

LineaPro 12 mini / 13 mini



CPU	ARM CortexM4
Buttons	2 scan buttons
Contactless Reader (optional)	NFC-A, ISO 14443 Type A NFC-B, ISO 14443 Type B NFC-F, Felica NFC-V, ISO 15693
Barcode Reader	2D Opticon MDI-4000 640 x 480 CMOS (optional) 2D Zebra SE4750 SR/MR 1280 x 960 CMOS (optional) 2D Zebra SE4770 1280 x 960 CMOS (optional)
Symbologies	BARCODE 1D: JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN-ISMN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/ Plessey POSTAL CODE: Chinese Post, Intelligent Mail Barcode, Korean Postal Authority code, POSTNET 2D CODE: Aztec Code, Aztec Runes, Chinese Sensible code, Codablock F, Composite codes, Data Matrix (ECC200), Passport MRZ (OCR-B), Maxi Code (mode 2~5), MicroPDF417, Micro QR Code, PDF417, QR code
Connectors	USB Type-C port Lightning connector (cradle) SAM holder Docking connector
Wired Communication	Serial communication (USB Type-C port) Serial communication (Docking connector)
Device Compatibility	iPhone 12 mini, iPhone 13 mini
Audio Features	Electromagnetic buzzer
Power Supply	DC 5 V through USB, DC 5 V through docking connector
Battery	Rechargeable Li-Ion Battery, 3.6 V, 2330 mAh, Fuel Gauge
Dimension W x D x H	73 x 155 x 28 mm
Weight	164 g
Operational Temperature	-10 °C to 40 °C / 5 to 90% RH
Storage Temperature	-20 °C to 50 °C / 5 to 90% RH
Drop Tested	1.2 m faces and edges
Other Box Contents	USB Type-A to USB Type-C cable